

DIFFUSION MEDIA CC-660 G (M6)

- **FINAL FILTRATION BARRIER** to paint damaging particles from the air intake stream
- **SELF EXTINGUISHING** according **DIN 53438-F1**
- **100% ADHESIVE SATURATION FOR MAXIMUM PROTECTION**
- **R0 RATING ON PARTICLE MIGRATION**
- **HIGH TEMPERATURE RESISTANT SCRIM** up to 350°F
- **QUALITY ASSURANCE BY DIN CERTCO WITH REGISTRATION NUMBER**

DESCRIPTION

Fine air filtration media specifically designed to be used in down-draft paint spray booths as the final filtration barrier to all paint damaging particles from the intake air stream. This ceiling filter or diffusion media ensures a completely uniform air distribution and an all round laminar air flow throughout the spray booth when applied in auto assembly plants and auto refinishing facilities. Synthetic fiber-based filter media developed and manufactured at Filtrair's high-tech media plant based in The Netherlands.

The filter media is constructed from selected high performance, nonbreakable fibers in a progressive density multi-layering technique allowing high depth loading to ensure high dust holding capacity with optimal lowest pressure drop performance. This media is thermally bonded and impregnated in full depth with a special tackifier coating to prevent any release of fibers and migration of paint damaging particles larger than 5 microns due to vibration in the system, even under varying temperature conditions.

CC-660 G is classified as R0 in accordance with the Filtrair migration test (see back page). This results in high fractional efficiency combined with a high dust loading capacity, a long filter life as well as low energy and maintenance costs.

HIGH TEMPERATURE SCRIM

The clean air side is particularly dense and smoothed. It is reinforced with a high temperature resistant and supporting woven open-mesh scrim. The temperature resistance of this special scrim is up to 350°F to prevent any discoloration.

FLAMMABILITY RATINGS

CC-660 G conforms to German fire classification standards (DIN53438-F1) and is self-extinguishing.

It is resistant to evaporated solvents and is produced in a 100% silicone-free environment.

QUALITY ASSURANCE

Constant quality is assured by independent quality control testing according to EN-779:2012 and by DIN CERTCO. The DIN-Logo with Filtrair's registration number PFE036/12, the M6 filter class and the Filtrair Logo with Brand Name are all imprinted on the media.

FEATURES AND BENEFITS

- **APPROVED BY MAJOR AUTOMOTIVE MANUFACTURERS** so it can be used with complete confidence.
- **FULL PENETRATION OF SPECIAL ADHESIVE** prevents any release of fibers and migration of particles larger than 5 microns.
- **GRADIENT DENSITY STRUCTURE** ensures a uniform air distribution and a laminar air flow throughout the spray booth.
- **APPROVED ACCORDING DAIMLER-CHRYSLER AND VOLKSWAGEN LACQUER TEST SPECIFICATIONS** by IPA Fraunhofer Institute.

APPLICATIONS

This particular and top of the line Filtrair ceiling filter or diffusion media is specially designed to be used in the ceiling center of paint spray facilities in auto assembly plants and down draft spray cabins of auto refinishing facilities.

This special media enhances a completely uniform air distribution and an all round optimal laminar air flow. Further, it acts as the final filtration barrier to paint damaging particles from the air stream which is an absolute requirement for high gloss and high-tech performance finishes.

DIFFUSION MEDIA CC-660 G (M6)


TECHNICAL DATA

Product	Unit	CC-660 G
Rated air flow	cfm	530
Air velocity	fpm	50
Initial pressure drop	"w.g.	0,22
Final pressure drop	"w.g.	1,81
Filter class per EN779:2012	-	M6
Average Arrestance	%	98
Average Efficiency (@0.4 µm)	%	70
Dust holding capacity (Ashrae dust) 450 Pa	oz/ft ²	160

APPLICATION PARAMETERS

Product	Unit	CC-660 G
Temperature resistance, constant	°F	≤ 210
Temperature resistance, short peaks	°F	< 350
Nominal thickness	inch	0.79
Relative humidity	%	100
Regenerable/washable	-	no
Roll sizes standaard		40" x 67'
		80" x 67'


FILTRAIR MIGRATION TEST




Filtrair Migration Test Classes	No. of particles(*)
R0	< 100
R1	< 1.000
R2	< 10.000
R3	< 100.000

(*) Number of particles larger than 10 microns per cubic meter counted on the clean air side


PRESSURE DROP vs AIR FLOW RATE



FRACTIONAL PARTICLE SIZE EFFICIENCY



DUSTLOADING vs PRESURE DROP vs EFFICIENCY



All data are average indicative values with usual manufacturing and testing tolerances. We reserve the right to modify performance data without prior notice. Specific performance data will require our written confirmation. Filtrair® is the registered trade mark of Filtrair bv.

