Filtration Group application example- Power Plants & Energy

Diesel treatment on emergency engines in nuclear plants



Power Plants & Energy

Initial situation

Especially in **nuclear power plants**, **safety** has the **highest priority**. For this reason even smallest processes are monitored in detail.

In Switzerland the **storage of the diesel** for the emergency engines **were identified as critical process**. The fuel, stored in 50.000 liter tanks, can be contaminated with water due to changes in temperature. This **water sinks to the ground of the tank and can cause problems** during the operation off the aggregates.



Solution statement

The **Filtration Group-facility in Hamburg is delivering fuel treatment systems** for the marine industry for several years now. The proven technology from the marine industry can nowadays also be found in several power plants. The **two stage systems** separates particles and dirt in the first filter stage and separates water in the coalescer stage afterwards.

The **remaining water content is too low for the microorganisms to grow** and avoids the dangerous dieselpest. The **Filtration Group FTS** can guarantee a continuously low remaining water content, which means that diesel pest will be no longer a problem for the customer. The **operational readiness** of the stored fuel **is assured at any time**.

Challenge

Four independent emergency power systems can be used in case of an incident. To ensure a frictionless operation of the emergency engines, a certain diesel quality is required. Low water content in the fuel is one of the main criteria. Water can cause corrosion, can be a risk for the engine injection nozzles or can build a good basis for microorganisms. This so called diesel pest is very dangerous, as this microorganisms create a kind of slime that can block filters, nozzles and pipes. In worst case the emergency engine is not able to start when it is required because of bad fuel quality.



Customer value

The **Filtration Group FTS** provides several advantages to the power plant operator:

- Long time storage of the fuel is no longer a risk
- Reduction of the free water in the fuel continuously below the critical limit
- Cost reduction due to lower maintenance requirements and reduced wear
- Replacement of no used fuels no longer necessary
- Inspections of the fuel quality can be reduced significantly









Schleifbachweg 45 74613 Öhringen Phone: +49 7941 / 6466 - 0

Mail: fm.de.sales@filtrationgroup.com

www.fluid.filtrationgroup.com

